



TECHNICAL DATA SHEET

BRIGHTO WOOD FINISH THINNER

General Description	Brighto Wood Finish Thinner is a solvent based thinner suitable for use in Brighto Wood Finish products like clear lacquers, opaque color topcoats and basecoats.
Pack Size	0.91 liters and 3.64 liters
Colour Range	Clear
Composition (Nominal)	Pigment: N/A Binder: N/A Solvent: Volatile Solvents BA, IPA, XYLENE
Density	0.84 ± 0.03; Theoretical
Film Thickness/Coat	N/A
Drying Times	Depends on temperature, humidity, air movements and film thickness
Touch Dry	N/A
Recoat	N/A
Theoretical Coverage	N/A
Application Thinning	Spray
Conventional Spray	Use Brighto Wood Finish Thinner 100 - 150% in Brighto Wood Finish products like clear lacquers, opaque color topcoats and basecoats.
Cleaning Up	Clean all equipment with Brighto Wood Finish Thinner immediately after use of NC products.
Surface Preparation	This is a thinner to be used in Brighto Wood Finish products like clear lacquers, opaque color topcoats and basecoats. (According to the product)
Flash Point	20°C



TECHNICAL DATA SHEET

BRIGHTO WOOD FINISH THINNER

Safety, health and environmental information

Highly inflammable. Keep container tightly closed, up right and out of reach of children. Keep away from the source of ignition e.g. cigarette, matchbox, lighter etc. Protect from extreme of temperature and store in a cool and dry place. Keep away from food, drink and animal feeding stuff. Keep container tightly closed. Wear suitable gloves, mask and safety goggles during application. Do not breathe in vapor and spray mist. May cause Irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness. Avoid contact with eyes and skin. In case of contact with eye rinse immediately with plenty of water and seek medical advice. If swallowed, rinse mouth with plenty of water (only if the person is conscious) show this container or label to a medical practitioner. Its vapor may cause drowsiness and dizziness. In case of fire use foam, dry powder, CO2 fire extinguisher. Never use water. Take precautionary measure against static charges. Use only in well ventilated place. Very toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Dispose of any paint waste in accordance with the appropriate environment quality regulation.

Any advice recommendations, information, assistance or service provided by Brighto Chemicals Pvt. Ltd. in relation to goods manufactured or marketed by it or their use or any applications is given in good faith without expressed or implied warranties.